

## MODEL NO. 60048 SUPERMAX STORE PANEL

### PARTS LIST

DESCRIPTION	No. REQ'D	PART NUMBER
Table Panel w/4 Tabs	1	302391
Counter Panel	1	301372
<i>Hardware Complete</i>	1	302333
5" O.D. Panel Clamp	4	302099*
90° Angle Bracket	4	302334*
1/4" x 3/4" Drive Rivet	4	168449*
3/8" Barrel Nut	12	804804*
3/8" Flat Washer	4	817410*
3/8" Heavy Hex Nut	4	804200*
3/8" x 1 1/2" P.B.H.C.S. w/Patch	8	812053*
3/8" x 3/8" Set Screw	4	811549*
3/8" x 3/4" Carriage Bolt	8	800252*

*Unless Otherwise Specified, All Units of Measure are Each  
\*Included in Hardware*

**Warning:** Small parts and hardware items may present a potential choking hazard. Promptly remove all unused parts from play area. Any bolt end protruding more than two full threads beyond the face of the nut causes risk of clothing entanglement. Promptly cut-off flush, file smooth, and treat to prevent corrosion.

**Note:** Peen Tee-Nuts and Flatwashers to match radius of pipe after assembly is complete.

**Note:** Loctite (supplied by others) should be used on all threaded hardware.

### INSTALLATION INSTRUCTIONS:

1. Attach Store Counter Panel to the Store/Table Panel using Angle Brackets, 3/8" x 3/4" Carriage Bolts and Barrel Nuts as shown in the assembly drawing.
2. Attach the assembled Store Panel to the Upright Posts using Panel Clamps (Refer to Panel Clamp Sub-assembly sheet for detail), with 3/8" x 1-1/2" P.B.H.C.S. w/ Patch, 3/8" Flat Washers and 3/8" Barrel Nuts.

**IMPORTANT!** Avoid creating any Gaps between the components, which fall between 3-1/2" and 9". It has been shown that such gaps create entrapment points which can trap a child and cause injury.

3. When the structure is finished and satisfactory, install Drive Rivets in all clamps to ensure clamps cannot slide down posts. See a Pipe Clamp subassembly sheet. ***It is very important that all Drive Rivets be installed prior to allowing use of the equipment, as clamps are not designed to support substantial weight without them.*** Eliminate sharp points and sharp edges (burring) on installed hardware like bolt, nuts, etc. Install resilient surfacing material under and around all equipment before allowing use. Refer to the *Safety Guidelines*.

### MAINTENANCE PROCEDURE:

Periodically check hardware for tightness, and tighten as necessary. Always check all parts for breakage or wear, and immediately put equipment out of service until any faulty parts are repaired or replaced. Check all decks for Plastisol-coating peeling and touch-up with Plastisol if necessary. Check for holes on deck, clean if necessary. Check periodically resilient surfacing for appropriate depth and remove extraneous materials that could cause injury, infection, or disease. Maintain detailed installation, inspection, maintenance, and repair records for each public-use playground equipment.

## MODEL NO. 60048 SUPERMAX STORE PANEL

