

MODEL NO. 60048 SUPERMAX STORE PANEL

PARTS LIST

DESCRIPTION	No. REQ'D	PART NUMBER
Table Panel w/4 Tabs	1	302391
Counter Panel	1	301372
Hardware Complete	1	302333
5" O.D. Panel Clamp	4	302099*
90° Angle Bracket	4	302334*
1/4" x 3/4" Drive Rivet	4	168449*
3/8" Barrel Nut	12	804804*
3/8" Flat Washer	4	817410*
3/8" Heavy Hex Nut	4	804200*
3/8" x 1 1/2" P.B.H.C.S. w/Patch	8	812053*
3/8" x 3/8" Set Screw	4	811549*
3/8" x 3/4" Carriage Bolt	8	800252*

** Included in Hardware*

Unless Otherwise Specified, All Units of Measure are Each

Warning: Small parts and hardware items may present a potential choking hazard. Promptly remove all unused parts from play area.

SPECIFICATIONS:

Clamps are cast from a 356 high-strength aluminum alloy with a baked on polyester powder-coated finish. Bracket is formed from 11-gauge galvanized steel powder coated after fabrication. Panels are cut from a sheet of high-density .850" thick extruded solid polyethylene with color molded in and UV-stabilized.

All hardware is stainless steel.

Weight: 56 lb. / 25.5 kg.

INSTALLATION INSTRUCTIONS:

1. Attach Store Counter Panel to the Store/Table Panel using Angle Brackets, 3/8" x 3/4" Carriage Bolts and Barrel Nuts as shown in the assembly drawing.
2. Attach the assembled Store Panel to the Upright Posts using Panel Clamps (Refer to Panel Clamp Sub-assembly sheet for detail), with 3/8" x 1-1/2" P.B.H.C.S. w/ Patch, 3/8" Flat Washers and 3/8" Barrel Nuts.

IMPORTANT! Avoid creating any Gaps between the components, which fall between 3-1/2" and 9". It has been shown that such gaps create entrapment points which can trap a child and cause injury.

3. When the structure is finished and satisfactory, install Drive Rivets in all clamps to ensure clamps cannot slide down posts. See a Pipe Clamp subassembly sheet. **It is very important that all Drive Rivets be installed prior to allowing use of the equipment, as clamps are not designed to support substantial weight without them.** Eliminate sharp points and sharp edges (burring) on installed hardware like bolt, nuts, etc. Install resilient surfacing material under and around all equipment before allowing use. Refer to the *Safety Guidelines*.

MAINTENANCE PROCEDURE:

Periodically check hardware for tightness, and tighten as necessary. Always check all parts for breakage or wear, and immediately put equipment out of service until any faulty parts are repaired or replaced. Check all decks for Plastisol-coating peeling and touch-up with Plastisol if necessary. Check for holes on deck, clean if necessary. Check periodically resilient surfacing for appropriate depth and remove extraneous materials that could cause injury, infection, or disease. Maintain detailed installation, inspection, maintenance, and repair records for each public-use playground equipment.

MODEL NO. 60048 SUPERMAX STORE PANEL

